

FuturePhone 160

GSM Fixed Wireless Phone



Product Features

- Speaker phone
- AC power supply
- Chargeable battery group
- A choice of 15 rings tones
- Last number redial
- Speed dialing with 99-numbers memory
- Adjustable ring and voice volume
- Scheduler and alarm functions
- A large phone book :250
- A large amount of SMS :200
- Display the incoming call number
- 128*64LCD display with status indicators

General Specification

Parameters	Frequency :	GSM: 850/900/ 1800/1900Mhz
	Environment temperature	-10℃—+55℃
	Humidity	0~95%
	Pressure	86-106Kpa
	Size	170mm*200mm*65mm
	Voltage	AC+25%
	Spurious transmit limit	less than -30dBm
	Modulation method	0.3GMSK
	LCD Screen	2.4 inch
	Battery capacity	700Ah li-ion
	Bandwidth	> 200KHZ
	Transmitting power	30/33dBm+2dB
	Maximum frequency error	+0.1ppm
	Input dynamic range	62dB
	Language	English
	External antenna	Combo interface
	Speaker	Support
	Technical standard	EGSM/GPRS/3GPP Release 99 compliant
	Internal memory	24M
	Flash	32M
	Language	English
	Voice code	FR/EFR/HR/AMR
	AMR code	Support
	Input method	English
	Alarm	Support
	Call log	10 + pcs as far
	SMS storage capacity	50 + items
	Contact capacity	50 + items in the phone
	Group SMS	Support
	Clock	Support

	Calculator	Support
	DTMF	Support
	Caller ID	Support
	Backlight time	Support
	Call duration	Support
	LCD Backlight adjustment	Support
	Programmable voice volume control	Support
	Programmable ring volume control	Support
	Hands- free mode	Support
	Speaker volume control in hands free operation	Support
	Key tone volume adjustments	Support
	Missed calls & incoming message indication on display	Support
	Call forwarding	Support
	Call wait/Call hold	Support
	Conference call	Support ,network dependent
	Call barring	Support
	Key digit input display	Support
	Banner display	Not support
	Time display	Support
	Operator name	Support
	No service/service indication	Support
	Voice call indication	Support
	Power status indication	Support
	Alarm indication	Support
	New SMS indication	Support
	Voice message indication	Support
	Lock cell	Support
	Lock operator	Support
	USB port	mini5pin USB
External port	Battery connector	3 PIN connector
	SIM interface	1.8V/3.0V SIM card
	External antenna	Combo
	External antenna	Around 2dBi
Antenna	Type	Li-on
Battery	Input	100~240V ~50-60 Hz
	Output	5V~500mA