

FutureFax GSM Voice and Fax Gateway



Features:

1. Based on GSM900MHz/1800MHz or 850/1900MHz
2. Supports reverse polarity
3. Can connect to PBX
4. Supports fax

Main Functions:

1. Making & answering calls after connecting to telephone set
2. Send/receive faxes through connection to analog fax machine
3. Able to connect with telephone set, PBX, billing machine, etc
4. Built-in PIN code protection featured with locking device/card/network
5. Caller ID
6. Signal intensity indicator, Working status indicator, fault indicator.

Technical Parameters:

- * Working Frequency
 - Rx (EGSM 900): 925~960MHz
 - Tx (EGSM 900): 880~915MHz
 - Rx (DCS 1800): 1805~1880MH
 - Tx (DCS 1800): 1710~1785MHz
- * Radio Frequency Power: 1W
- * Rx Sensitivity: <-104dBm
- * Antenna Gain: >1.5Db
- * Power supply voltage: 12V

Package Information:

Product Size: 181(L) x 125(W) x 35 (H)mm
Weight: 333g/pc
Package: 1pc/box; 20boxes/carton
Carton size: 58.5*29.5*37.5CM

Distributor: FCT Technologies (Pty) Ltd
Michael Wilkinson Sales and Marketing Director
Cell: +27 83 2519778
Email: ftech@telkomsa.net
Web: www.fcttech.co.za